

INTELLIGENT



INNOVATIVE
DESIGN



EASY
TO INSTALL



SMART
THINGS



Ditec DAS200 - DAS200HD - DAS200T

EN

Automation for sliding doors
Sliding to the future

Data sheet

Technical specifications

	DAS200	DAS200HD	DAS200T
Description	automation for sliding doors	automation for sliding doors	automation for telescopic sliding doors
Max. wing weight	120 kg (1 wing) 200 kg (2 wings)	150 kg (1 wing) 280 kg (2 wings)	240 kg (1+1 wings) 320 kg (2+2 wings)
Clear passage	715 - 3215 mm (1 wing) 790 - 3240 mm (2 wings)	715 - 3215 mm (1 wing) 840 - 3240 mm (2 wings)	1103 - 4320 mm (1+1 wings) 1600 - 4320 mm (2+2 wings)
Product dimensions (HxWxL)	120 x 185 x L mm	120 x 185 x L mm	120 x 265 x L mm
Max. opening and closing speed (2 wings)	1.6 m/s	1.6 m/s	1.6 m/s
Power supply	110 V ~ /240 V ~ 50/60 Hz	110 V ~ /240 V ~ 50/60 Hz	110 V ~ /240 V ~ 50/60 Hz
Power supply rated power	75 W	150 W	150 W
Accessories power supply	24 V= /0.64 A	24 V= /1 A	24 V= /1 A
Protection rating	IP20	IP20	IP20
Approvals	TÜV	TÜV	TÜV
Control panel	1DAS20QE	1DAS20HDQE	1DAS20HDQE

Main functions

	DAS200	DAS200HD - DAS200T
Control panel	1DAS20QE	1DAS20HDQE
Power supply	110 V ~ /240 V ~ 50/60 Hz	110 V ~ /240 V ~ 50/60 Hz
Batteries	12 V or 24 V (optional)	12 V or 24 V (optional)
Hold force adjustment	■	■
Obstacle detection (stop while opening or reverse while closing)	■	■
Automatic passage opening width selection (depending on the flow of people)	■	■
Hold open time	0 - 60 s	0 - 60 s
Presence hold open time	0 - 60 s	0 - 60 s
Interlock function	■ (optional with DAS902MP)	■ (optional with DAS902MP)
Opening safety function (speed limiting)	■	■
Battery energy saving function in case of power failure	■	■
Emergency reverse with presence sensor	■ (compliant with EN 16005)	■ (compliant with EN 16005)
Safety test and safety monitoring function	■ (compliant with EN 16005)	■ (compliant with EN 16005)
Independent opening / closing commands	■ (optional with DAS902MP)	■ (optional with DAS902MP)
"Nurse" function	■ (optional with DAS902MP)	■ (optional with DAS902MP)
"Fire alarm" function	■ (optional with DAS902MP)	■ (optional with DAS902MP)
Emergency opening function	■ (optional with DAS902MP)	■ (optional with DAS902MP)



Entrematic Italy S.p.A.

Largo U. Boccioni, 1 • 21040 Origgio (VA) • Italy
 Tel +39 02 963911 • Fax: +39 02 9650314
 ditec@entrematic.com
 www.ditecentrematic.com

04/2020
 Ditec DAS200 - EN